Kodak Alaris

# Color Toggle

(Patch 4)

Version 8

**Sized for printing unscaled on A4 paper**

**To verify this patch page has been printed with the proper scaling, measure the vertical and horizontal dimension lines and the spacing from the edge of page to start of first bar.**

1) **The vertical dimension line must be exactly 8.27 inches (210mm).**
2) **The horizontal dimension line must be exactly 5 inches (127mm).**
3) **The distance from edge of page to start of first bar must be 0.5 inches (12.7mm)**

**If the separator sheet is not printed as described the scanner will not reliably recognize the patch code.**

Printing Instructions:

For proper operation this scanner separator sheet must be printed with a scale of 100% or unscaled on paper that matches the noted size of the image. (check the printer options or advanced printer properties when printing)
The printing should be done in black such that the black bars reflect less than 20% of the infrared and visible light.
The paper used should be white or light pastel colored such that at least 65% of the infrared and visible light is reflected in none printer areas.

Wide black bars must be exactly 0.2in.
Narrow black bars and white voids must be exactly 0.08in.
There should be 0.3in of white boarder from edge of page to start of vertical bars and 1.5in to horizontal bars.

This dimension line must measure 210mm (8.27in.)

This dimension line must measure 127mm (5.0in)